



C1FA18002



INTERFACE	Ethernet 10/100/1000 via RJ45 x1
POWER	PoE 802.3at Class 4
POWER CONSUMPTION	11.5W
VIDEO OUTPUT	640x320@30fps 1920x960@30fps 1920x1080@30fps 3840x1920@30fps 2880x5760@15fps H.264 in RTP/RTSP streaming
CONTROL	DHCP/ DNS/ NTP/ HTTP/ HTTPS/ IPv4/ TCP/ UDP/ RTP/ RTSP/ RTMP/ ONVIF (Profile S)
OPTICAL FEATURES	360° (Horizontal) / 180° (Vertical) / F2.2
AUDIO	Microphone x1
PHYSICAL FEATURES	68 x 68 x 200mm(Not including accessory cap, lens, PoE Cable)
	Approximately 1.03kg
	1/4" camera screw hole
	PMS 877 C Aluminum / Anodized, IEC60529_IP66
	Humidity(IEC 60068-2-78) 、 Salt Test (MIL-810F section 509.4), Solar Testing(IEC-60068), Thermal Shock(MIL-810)
TEMPERATURE	-10°C to 50°C operating
HUMIDITY	5% to 90% RH
SHOCK RESISTANCE	Drop Testing(IEC-60950-01), 6 feet(1.83 meters), concrete floor, Top and bottom face, No camera lens side.
VIBRATION RESISTANCE	Vibration(IEC 60068-2-64), Random vibration along three perpendicular axes for 2 hours with 0.41G RMS acceleration level over 3 to 500Hz
ELECTRICAL SAFETY	CB: IEC 62368-1 : 2018 ED.3 EU / CE: EN 62368-1 ED.2 New Zealand / Australia: AS/NZS 62368-1 ED.2 test Taiwan / safety: CNS 15598-1
EMI/EMS REGULATION	Taiwan / EMC: BSMI(CNS15936) EU / CE: EN 55032 / EN 55035, Class A USA / FCC: 47 CFR Part15, Subpart B, Class A Canada / ISED: ICES-003, Issue 7, Class A AS/NZS: CISPR 32, Class A
ENVIRONMENTAL REGULATION	GP Compliance
COMPLIANCE	NDAA